


螺帽公稱型號	螺桿軸 外徑 d	導程 l	滾珠 直徑 D_w	滾珠間距 圓直徑 d_m	螺桿軸螺 紋溝底徑 d	有效圈數 圈數 × 牙數	基本額定負載 (N)		軸向 最大 間隙	螺帽尺寸 外徑 D
							動態額定值 C_a	靜態額定值 C_{0a}		
RNFBL 1006A2.5S	10	6	2.381	10.65	8.1	2.5×1	2830	4810	0.10	26
RNFBL 1208A2.5S	12	8	2.778	12.65	9.6	2.5×1	3730	6560	0.10	29
RNFBL 1404A3.5S	14	4	2.778	14.5	11.5	3.5×1	5370	10800	0.10	31
RNFBL 1405A2.5S	14	5	3.175	14.5	11.0	2.5×1	5260	9720	0.10	32
RNFBL 1808A3.5S	18	8	4.762	18.5	13.6	3.5×1	13200	25800	0.15	50
RNFBL 2005A2.5S	20	5	3.175	20.5	17.0	2.5×1	6360	14200	0.10	40
RNFBL 2010A2.5S	20	10	4.762	21.25	16.2	2.5×1	10900	21800	0.15	52
RNFBL 2505A2.5S	25	5	3.175	25.5	22.0	2.5×1	7070	18200	0.10	43
RNFBL 2505A5S						2.5×2	12800	36300		
RNFBL 2510A2.5S	25	10	6.35	26	19.0	2.5×1	17500	35200	0.20	60
RNFBL 2510A5S						2.5×2	31800	70300		
RNFBL 2806A2.5S	28	6	3.175	28.5	25.0	2.5×1	7430	20300	0.10	50
RNFBL 2806A5S						2.5×2	13500	40600		
RNFBL 3210A2.5S	32	10	6.35	33.75	27.0	2.5×1	19700	46100	0.20	67
RNFBL 3210A5S						2.5×2	35700	92200		
RNFBL 3610A2.5S	36	10	6.35	37	30.0	2.5×1	21000	51000	0.20	70
RNFBL 3610A5S						2.5×2	38100	102000		
RNFBL 4010A5S	40	10	6.35	41.75	35.0	2.5×2	40100	116000	0.20	76

備註：1. 螺桿軸全長有時會較加工上用之 L_s 尺寸稍微長一些。

2. 交貨時，將分開提供裝配在假軸上之螺帽組裝品和螺桿軸。

3. 螺桿軸公稱型號上之**，係標示標準螺桿軸長度除以100mm後所得出之值。



單位：mm

法蘭部		螺帽尺寸						螺帽		假軸		螺桿軸			軸之公稱型號	軸 (每米長) 重量 (kg)
		長度 全長		安裝孔		注油孔		重量 (kg)	外徑 d_o	內徑 d_i	標準螺桿軸長度 L_s					
A	H	B	L	(C)	W	X	Q				T					
42	29	8	36	3	34	4.5	M3×0.5	5.0	0.16	8.1	6.1	400	800	RS1006A **	0.56	
45	32	8	44	3	37	4.5	M3×0.5	5.5	0.21	9.6	7.6	400	800	RS1208A **	0.81	
50	37	10	40	4	40	4.5	M6×1	5.0	0.25	11.5	9.5	500	1000	RS1404A **	1.02	
50	38	10	40	4	40	4.5	M6×1	5.0	0.26	11.0	9.0	500	1000	RS1405A **	1.00	
80	60	12	61	4	65	6.6	M6×1	6.0	1.00	13.6	11.6	500	1000	1500	RS1808A **	1.60
60	46	10	40	4	50	4.5	M6×1	5.0	0.37	17.0	14.6	500	1000	2000	RS2005A **	2.17
82	64	12	61	5	67	6.6	M6×1	6.0	1.05	16.2	13.8	500	1000	2000	RS2010A **	2.18
67	50	10	40	4	55	5.5	M6×1	5.0	0.40	22.0	19.6	1000	2000	2500	RS2505A **	3.47
			0.50													
96	72	15	66	5	78	9.0	M6×1	7.5	1.52	19.0	16.6	1000	2000	2500	RS2510A **	3.13
			1.99													
80	60	12	47	5	65	6.6	M6×1	6.0	0.70	25.0	22.6	1000	2000	2500	RS2806A **	4.47
			0.87													
103	78	15	67	5	85	9.0	M6×1	7.5	1.72	27.0	24.6	1000	2000	3000	RS3210A **	5.53
			2.25													
110	82	17	69	5	90	11.0	M6×1	8.5	1.97	30.0	27.6	1000	2000	3000	RS3610A **	6.91
			2.53													
116	88	17	99	5	96	11.0	M6×1	8.5	2.86	35.0	31.8	2000	3000	4000	RS4010A **	8.87

備註：4. 庫存品沒有進行表面處理。根據客戶要求，可用磷酸鹽護膜等進行表面處理。

5. 當軸徑在14mm以下時，為合成樹脂密封墊；當軸徑在16mm以上時，為薄密封墊。