




Bore Diameter 20 – 55 mm




Cylindrical Bore



Tapered Bore



Without an Oil Groove or Holes



**Dynamic Equivalent Load**

$$P = XF_r + YF_a$$

$F_a/F_r \leq e$		$F_a/F_r > e$	
X	Y	X	Y
1	$Y_3$	0.67	$Y_2$

**Static Equivalent Load**

$$P_0 = F_r + Y_0 F_a$$

The values of  $e$ ,  $Y_2$ ,  $Y_3$ , and  $Y_0$  are given in the table below.


Boundary Dimensions (mm)				Basic Load Ratings				Limiting Speeds		Bearing
$d$	$D$	$B$	$r_{min.}$	$C_r$	$C_{0r}$	{kgf}		(min <sup>-1</sup> )		
				(N)		$C_r$	$C_{0r}$	Grease	Oil	Cylindrical Bore
20	52	15	1.1	29 300	26 900	2 980	2 740	6 300	8 200	<b>21304CDE4</b>
25	52	18	1	37 500	37 000	3 850	3 800	7 100	9 000	<b>22205CE4</b>
	62	17	1.1	43 000	40 500	4 350	4 150	5 300	6 700	<b>21305CDE4</b>
30	62	20	1	50 000	50 000	5 100	5 100	6 000	7 500	<b>22206CE4</b>
	72	19	1.1	55 000	54 000	5 600	5 500	4 500	6 000	<b>21306CDE4</b>
35	72	23	1.1	69 000	71 000	7 050	7 200	5 300	6 700	<b>22207CE4</b>
	80	21	1.5	71 500	76 000	7 250	7 750	4 000	5 300	<b>21307CDE4</b>
40	80	23	1.1	90 500	99 500	9 200	10 100	6 000	7 500	<b>22208EAE4</b>
	90	23	1.5	94 500	111 000	9 600	11 300	5 300	7 000	<b>21308EAE4</b>
	90	33	1.5	136 000	153 000	13 900	15 600	4 500	6 000	<b>22308EAE4</b>
45	85	23	1.1	94 500	111 000	9 600	11 300	5 300	7 000	<b>22209EAE4</b>
	100	25	1.5	119 000	144 000	12 100	14 600	4 500	5 600	<b>21309EAE4</b>
	100	36	1.5	166 000	195 000	16 900	19 900	4 000	5 300	<b>22309EAE4</b>
50	90	23	1.1	99 000	119 000	10 100	12 100	5 000	6 300	<b>22210EAE4</b>
	110	27	2	142 000	174 000	14 500	17 800	4 300	5 300	<b>21310EAE4</b>
	110	40	2	197 000	234 000	20 000	23 900	3 800	4 800	<b>22310EAE4</b>
55	100	25	1.5	119 000	144 000	12 100	14 600	4 500	5 600	<b>22211EAE4</b>
	120	29	2	142 000	174 000	14 500	17 800	4 300	5 300	<b>21311EAE4</b>
	120	43	2	234 000	292 000	23 800	29 800	3 400	4 300	<b>22311EAE4</b>

**Note** (1) The suffix K represents bearings with tapered bores (taper 1 : 12).


Numbers	Abutment and Fillet Dimensions (mm)					Constant	Axial Load Factors			Mass (kg)
	$d_a$		$D_a$		$r_a$		$e$	$Y_2$	$Y_3$	
Tapered Bore <sup>(1)</sup>	min.	max.	max.	min.	max.					approx.
<b>21304CDKE4</b>	27	28	45	42	1	0.31	3.2	2.1	2.1	0.17
<b>22205CKE4</b> <b>21305CDKE4</b>	31	31	46	45	1	0.35	2.9	1.9	1.9	0.17
	32	34	55	51	1	0.29	3.4	2.3	2.3	0.26
<b>22206CKE4</b> <b>21306CDKE4</b>	36	37	56	54	1	0.33	3.1	2.1	2.0	0.27
	37	40	65	59	1	0.28	3.6	2.4	2.3	0.39
<b>22207CKE4</b> <b>21307CDKE4</b>	42	43	65	63	1	0.32	3.1	2.1	2.0	0.42
	44	47	71	67	1.5	0.28	3.6	2.4	2.4	0.53
<b>22208EAKE4</b> <b>21308EAKE4</b> <b>22308EAKE4</b>	47	49	73	70	1	0.28	3.6	2.4	2.4	0.50
	49	54	81	75	1.5	0.25	3.9	2.7	2.6	0.73
	49	52	81	77	1.5	0.35	2.8	1.9	1.9	0.98
<b>22209EAKE4</b> <b>21309EAKE4</b> <b>22309EAKE4</b>	52	54	78	75	1	0.25	3.9	2.7	2.6	0.55
	54	65	91	89	1.5	0.23	4.3	2.9	2.8	0.96
	54	59	91	86	1.5	0.34	2.9	2.0	1.9	1.34
<b>22210EAKE4</b> <b>21310EAKE4</b> <b>22310EAKE4</b>	57	60	83	81	1	0.24	4.3	2.9	2.8	0.61
	60	72	100	98	2	0.23	4.4	3.0	2.9	1.21
	60	64	100	93	2	0.35	2.8	1.9	1.9	1.78
<b>22211EAKE4</b> <b>21311EAKE4</b> <b>22311EAKE4</b>	64	65	91	89	1.5	0.23	4.3	2.9	2.8	0.81
	65	72	110	98	2	0.23	4.4	3.0	2.9	1.58
	65	73	110	103	2	0.34	2.9	2.0	1.9	2.3

**Remarks** 1. An oil groove and holes are standard for the EA type.  
2. For the dimensions of adapters and withdrawal sleeves, refer to Pages **B354 – B355**, and **B362**.


Bore Diameter 60 – 85 mm




Cylindrical Bore



Tapered Bore



Without an Oil Groove or Holes



**Dynamic Equivalent Load**

$$P = XF_r + YF_a$$

$F_a/F_r \leq e$		$F_a/F_r > e$	
X	Y	X	Y
1	$Y_3$	0.67	$Y_2$

**Static Equivalent Load**

$$P_0 = F_r + Y_0 F_a$$

The values of  $e$ ,  $Y_2$ ,  $Y_3$ , and  $Y_0$  are given in the table below.

Boundary Dimensions (mm)	Basic Load Ratings				Limiting Speeds		Bearing			
	$d$	$D$	$B$	$r_{min.}$	(N)	{kgf}		( $min^{-1}$ )		
				$C_r$	$C_{0r}$	$C_r$	$C_{0r}$	Grease	Oil	Cylindrical Bore
<b>60</b>	95	26	1.1	98 000	141 000	10 000	14 400	3 600	4 500	<b>23012CE4</b>
	110	28	1.5	142 000	174 000	14 500	17 800	4 300	5 300	<b>22212EAE4</b>
	130	31	2.1	190 000	244 000	19 400	24 900	3 400	4 300	<b>21312EAE4</b>
	130	46	2.1	271 000	340 000	27 600	35 000	3 200	4 000	<b>22312EAE4</b>
<b>65</b>	120	31	1.5	177 000	230 000	18 000	23 500	3 800	4 800	<b>22213EAE4</b>
	140	33	2.1	212 000	275 000	21 600	28 000	3 200	4 000	<b>21313EAE4</b>
	140	48	2.1	300 000	380 000	30 500	38 500	3 000	3 800	<b>22313EAE4</b>
<b>70</b>	125	31	1.5	180 000	232 000	18 300	23 600	3 600	4 500	<b>22214EAE4</b>
	150	35	2.1	250 000	325 000	25 400	33 500	3 000	3 800	<b>21314EAE4</b>
	150	51	2.1	340 000	435 000	34 500	44 000	2 800	3 400	<b>22314EAE4</b>
<b>75</b>	130	31	1.5	190 000	244 000	19 400	24 900	3 400	4 300	<b>22215EAE4</b>
	160	37	2.1	250 000	325 000	25 400	33 500	3 000	3 800	<b>21315EAE4</b>
	160	55	2.1	390 000	505 000	39 500	51 500	2 600	3 200	<b>22315EAE4</b>
<b>80</b>	140	33	2	212 000	275 000	21 600	28 000	3 200	4 000	<b>22216EAE4</b>
	170	39	2.1	284 000	375 000	29 000	38 000	2 800	3 600	<b>21316EAE4</b>
	170	58	2.1	435 000	565 000	44 000	58 000	2 400	3 000	<b>22316EAE4</b>
<b>85</b>	150	36	2	250 000	325 000	25 400	33 500	3 000	3 800	<b>22217EAE4</b>
	180	41	3	289 000	395 000	29 500	40 000	2 800	3 600	<b>21317EAE4</b>
	180	60	3	480 000	630 000	49 000	64 000	2 200	2 800	<b>22317EAE4</b>

**Note** (1) The suffix K represents bearings with tapered bores (taper 1 : 12).

Numbers	Abutment and Fillet Dimensions (mm)					Constant	Axial Load Factors			Mass (kg)
	Tapered Bore(1)		$d_a$	$D_a$	$r_a$		$e$	$Y_2$	$Y_3$	
	min.	max.	max.	min.	max.					approx.
<b>23012CKE4</b> <b>22212EAKE4</b> <b>21312EAKE4</b> <b>22312EAKE4</b>	67	68	88	85	1	0.26	3.9	2.6	2.5	0.68
	69	72	101	98	1.5	0.23	4.4	3.0	2.9	1.1
	72	87	118	117	2	0.22	4.5	3.0	3.0	1.98
	72	79	118	111	2	0.34	3.0	2.0	1.9	2.89
<b>22213EAKE4</b> <b>21313EAKE4</b> <b>22313EAKE4</b>	74	80	111	107	1.5	0.24	4.2	2.8	2.7	1.51
	77	94	128	126	2	0.22	4.6	3.1	3.0	2.45
	77	84	128	119	2	0.33	3.0	2.0	2.0	3.52
<b>22214EAKE4</b> <b>21314EAKE4</b> <b>22314EAKE4</b>	79	84	116	111	1.5	0.23	4.3	2.9	2.8	1.58
	82	101	138	135	2	0.22	4.6	3.1	3.0	3.0
	82	91	138	129	2	0.33	3.0	2.0	2.0	4.28
<b>22215EAKE4</b> <b>21315EAKE4</b> <b>22315EAKE4</b>	84	87	121	117	1.5	0.22	4.5	3.0	3.0	1.64
	87	101	148	134	2	0.22	4.6	3.1	3.0	3.64
	87	97	148	137	2	0.33	3.0	2.0	2.0	5.26
<b>22216EAKE4</b> <b>21316EAKE4</b> <b>22316EAKE4</b>	90	94	130	126	2	0.22	4.6	3.1	3.0	2.01
	92	109	158	146	2	0.23	4.4	3.0	2.9	4.32
	92	103	158	145	2	0.33	3.0	2.0	2.0	6.23
<b>22217EAKE4</b> <b>21317EAKE4</b> <b>22317EAKE4</b>	95	101	140	135	2	0.22	4.6	3.1	3.0	2.54
	99	108	166	142	2.5	0.24	4.3	2.9	2.8	5.2
	99	110	166	155	2.5	0.33	3.1	2.1	2.0	7.23

**Remarks** 1. An oil groove and holes are standard for the EA type.  
2. For the dimensions of adapters and withdrawal sleeves, refer to Pages **B355 – B357**, and **B362**.





















# SPHERICAL ROLLER BEARINGS




Bore Diameter 850 – 1400 mm



Cylindrical Bore



Tapered Bore



**Dynamic Equivalent Load**

$$P = XF_r + YF_a$$

$F_a/F_r \leq e$		$F_a/F_r > e$	
X	Y	X	Y
1	$Y_3$	0.67	$Y_2$

**Static Equivalent Load**

$$P_0 = F_r + Y_0 F_a$$

The values of  $e$ ,  $Y_2$ ,  $Y_3$ , and  $Y_0$  are given in the table below.

Boundary Dimensions (mm)				Basic Load Ratings (N) / (kgf)				Limiting Speeds (min <sup>-1</sup> )		Bearing
$d$	$D$	$B$	$r$ min.	$C_r$	$C_{0r}$	$C_r$	$C_{0r}$	Grease	Oil	
<b>850</b>	1 120	200	6	6 100 000	15 200 000	620 000	1 550 000	190	240	<b>239/850CAE4</b>
	1 220	272	7.5	9 300 000	21 400 000	945 000	2 190 000	180	220	<b>230/850CAE4</b>
	1 220	365	7.5	11 600 000	28 300 000	1 180 000	2 890 000	150	190	<b>240/850CAE4</b>
	1 500	515	15	22 300 000	45 500 000	2 270 000	4 650 000	120	160	<b>232/850CAE4</b>
<b>900</b>	1 180	206	6	6 600 000	16 700 000	670 000	1 700 000	180	220	<b>239/900CAE4</b>
	1 280	280	7.5	9 850 000	22 800 000	1 000 000	2 330 000	160	200	230/900CAE4
	1 280	375	7.5	12 800 000	31 500 000	1 300 000	3 250 000	140	180	<b>240/900CAE4</b>
	1 580	515	15	23 400 000	47 500 000	2 380 000	4 850 000	110	140	<b>232/900CAE4</b>
<b>950</b>	1 250	224	7.5	7 600 000	19 900 000	775 000	2 030 000	160	200	<b>239/950CAE4</b>
	1 360	300	7.5	11 300 000	26 500 000	1 160 000	2 710 000	150	190	<b>230/950CAE4</b>
	1 360	412	7.5	14 500 000	36 500 000	1 480 000	3 700 000	120	160	<b>240/950CAE4</b>
	1 660	530	15	24 700 000	50 500 000	2 520 000	5 150 000	100	130	<b>232/950CAE4</b>
<b>1 000</b>	1 320	236	7.5	8 200 000	21 700 000	835 000	2 210 000	150	190	239/1000CAE4
	1 420	308	7.5	11 900 000	28 100 000	1 210 000	2 860 000	140	170	230/1000CAE4
	1 420	412	7.5	15 300 000	38 500 000	1 560 000	3 950 000	110	150	<b>240/1000CAE4</b>
<b>1 060</b>	1 400	250	7.5	9 300 000	24 400 000	950 000	2 490 000	130	170	<b>239/1060CAE4</b>
	1 500	325	9.5	13 000 000	31 500 000	1 330 000	3 200 000	120	160	<b>230/1060CAE4</b>
	1 500	438	9.5	16 800 000	43 000 000	1 720 000	4 350 000	100	130	240/1060CAE4
<b>1 120</b>	1 580	345	9.5	15 400 000	38 000 000	1 570 000	3 850 000	110	140	230/1120CAE4
	1 580	462	9.5	18 700 000	49 500 000	1 910 000	5 050 000	95	120	<b>240/1120CAE4</b>
<b>1 180</b>	1 660	475	9.5	20 200 000	52 500 000	2 060 000	5 350 000	85	110	240/1180CAE4
<b>1 250</b>	1 750	500	9.5	21 000 000	59 500 000	2 140 000	6 050 000	75	100	<b>240/1250CAE4</b>
<b>1 320</b>	1 850	530	12	22 600 000	63 500 000	2 310 000	6 500 000	67	85	<b>240/1320CAE4</b>
<b>1 400</b>	1 950	545	12	24 500 000	65 000 000	2 500 000	6 650 000	60	75	<b>240/1400CAE4</b>

**Note** (!) The suffix K or K30 represents bearings with tapered bores (taper 1 : 12 or 1 : 30).

Numbers	Abutment and Fillet Dimensions (mm)				Constant	Axial Load Factors			Mass (kg)
	$d_a$ min.	$d_a$ max.	$D_a$ min.	$r_a$ max.		$e$	$Y_2$	$Y_3$	
<b>239/850CAKE4</b> <b>230/850CAKE4</b>	878 886	1 092 1 184	1 046 1 109	5 6	0.16 0.21	6.2 4.8	4.2 3.2	4.1 3.1	523 1 020
<b>240/850CAK30E4</b> <b>232/850CAKE4</b>	886 914	1 184 1 436	1 093 1 274	6 12	0.28 0.35	3.6 2.8	2.4 1.9	2.4 1.9	1 350 3 890
<b>239/900CAKE4</b> 230/900CAKE4	928 936	1 152 1 244	1 103 1 169	5 6	0.16 0.20	6.4 4.9	4.3 3.3	4.2 3.2	591 1 160
<b>240/900CAK30E4</b> <b>232/900CAKE4</b>	936 964	1 244 1 516	1 147 1 354	6 12	0.28 0.33	3.6 3.0	2.4 2.0	2.4 2.0	1 520 4 300
<b>239/950CAKE4</b> <b>230/950CAKE4</b>	986 986	1 214 1 324	1 169 1 241	6 6	0.16 0.21	6.3 4.8	4.2 3.2	4.1 3.2	732 1 400
<b>240/950CAK30E4</b> <b>232/950CAKE4</b>	986 1 014	1 324 1 596	1 219 1 428	6 12	0.28 0.32	3.6 3.1	2.4 2.1	2.3 2.1	1 880 4 800
239/1000CAKE4 230/1000CAKE4 <b>240/1000CAK30E4</b>	1 036 1 036 1 036	1 284 1 384 1 384	1 229 1 298 1 275	6 6 6	0.16 0.20 0.27	6.4 4.9 3.7	4.3 3.3 2.5	4.2 3.2 2.4	881 1 560 2 010
<b>239/1060CAKE4</b> <b>230/1060CAKE4</b> 240/1060CAK30E4	1 096 1 104 1 104	1 364 1 456 1 456	1 302 1 368 1 346	6 8 8	0.16 0.21 0.28	6.1 4.9 3.6	4.1 3.3 2.4	4.0 3.2 2.4	1 030 1 790 2 410
230/1120CAKE4 <b>240/1120CAK30E4</b>	1 164 1 164	1 536 1 536	1 444 1 421	8 8	0.20 0.27	5.0 3.7	3.4 2.5	3.3 2.5	2 120 2 790
240/1180CAK30E4	1 224	1 616	1 494	8	0.27	3.7	2.5	2.4	3 180
<b>240/1250CAK30E4</b>	1 294	1 706	1 579	8	0.25	4.0	2.7	2.6	3 700
<b>240/1320CAK30E4</b>	1 374	1 796	1 656	10	0.26	3.9	2.6	2.6	4 400
<b>240/1400CAK30E4</b>	1 454	1 896	1 767	10	0.25	4.0	2.7	2.6	4 900